

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

175-296

S

PATENT SPECIFICATION

DRAWINGS ATTACHED

Inventor: FREDERICK RICHARD STALLARD

962,127



Date of filing Complete Specification March 18, 1963.

Application Date Dec. 29, 1961.

Complete Specification Published June 24, 1964.

© Crown Copyright 1964.

962,127

No. 46754/61.

GT. BRIT.
DIV. 420

00175

Index at acceptance:—E1 F(31D1, 31D2, 31F); B4 C(1B1A, 3B, 3E, 3H, 7, 15, 16)

International Classification:—E 21 b (E 21 c)

COMPLETE SPECIFICATION

Earth and the like Boring or Drilling Apparatus

We, ENGLISH DRILLING EQUIPMENT COMPANY LIMITED, a British Company, and FRANK WALMSLEY a British subject, both of the Company's address of Palace Chambers, Bridge Street, Westminster, London, S.W.1., do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

THIS INVENTION relates to boring or drilling apparatus used for earth, rock and like boring or drilling operations.

In such apparatus a drill bit or cutting tool is carried at one end of a "string" of drill rods which receive and transmit to said bit or tool a rotary and feed motion from a suitable source. With such apparatus it is known to give simultaneously with the rotary and feed motion for cutting purposes a percussive action to the drill bit or tool, particularly when, for example, hard strata is being bored. It is an object of the present invention to give a percussive action to the drill bit or tool by means which, though simple in construction is efficient in operation.

According to the invention apparatus for applying percussive blows to the drill bit of boring or drilling apparatus comprises a cylinder member adapted for connection to the drill rod string, a hammer like piston member operating in said cylinder member, inlet and exhaust ports in the cylinder wall for passage of a pressurized gaseous medium, and passage means in said piston member for controlling passage of said gaseous medium to and from said cylinder member through said inlet and exhaust ports respectively, the opening and closing of said ports being controlled by said piston member during movement of the latter by the gaseous medium in a manner whereby the hammer like piston

member provides percussive blows for the drill bit.

In one form of the invention the cylinder member is adapted for connection to the last drill rod at the outer or lower end of the drill rod string, and an extension of the drill bit is carried by and movable relative to the outer or lower end of the cylinder member, a projecting or tail portion of the piston member applying the percussive blows to the drill bit extension. In this form the cylinder member may comprise inner and outer tubular members spaced apart to form an annular chamber divided into compressed air supply and exhaust sections, the inlet and exhaust ports being formed in the inner tubular member and opening into said supply and exhaust sections of the annular chamber respectively. The compressed air can be conveniently supplied through the usual bore of the drill rod string to passage means formed in a cylinder head and leading to the supply section of the annular chamber.

In another form of the invention one end of the cylinder member is connected to one part of a two-part telescoping unit, the other part of which is adapted for connection to the first drill rod of the drill rod string, and the other end of the cylinder is connected to a driving quill providing the rotary and feed motion to the drill rod string, the hammer like piston member applying the percussive blows to an extension or stem portion of said other part of the two part telescoping unit and thus through the drill rod string to the drill bit. In this form of the invention, the cylinder member rotates within a non-rotary air swivel assembly comprising a sleeve member surrounding and spaced from the cylinder members to form an annular chamber divided into a compressed air supply section and an air exhaust section into which the inlet and ex-

[Price 4s. 6d.]

haust ports of the cylinder member open respectively.

Suitable constructions of both of the above referred to forms of the invention are described by way of example in what follows, and are illustrated in the accompanying drawings in which:

Fig. 1 is a longitudinal sectional view of a vertical boring or drilling type of apparatus constructed according to the invention, whilst

Fig. 2 is a detail thereof to be referred to later,

Fig. 3 is a view similar to Fig. 1 but showing a modified form of the cylinder and piston members, whilst

Fig. 4 is a detail to be referred to later,

Fig. 5 is a longitudinal sectional view of another form of apparatus which is particularly adapted for boring or drilling horizontally, or inclined thereto, whilst

Fig. 6 is an external view at right angles thereto.

As shown in Figs. 1 and 2 the cylinder member is indicated generally at *a* and is provided with a cylinder head *b* spaced from a drill rod connector *c* by a cushion assembly *d*. The latter comprises an inner member *d'* screw-threaded into head *b*, and an outer sleeve *d''* which is splined or keyed to *d'* and also screw-threaded into rod connector *c*. This drill rod connector *c* is screw-threaded at its outer reduced end at *c'* for connection to the last drill rod (not shown) forming the outer end of the drill rod string.

The cylinder member *a* comprises an outer tube *a'* and an inner liner tube *a''*, the tube *a'* being internally threaded at its upper ends for connection to the cylinder head *b*. The upper end of the liner tube *a''* of the cylinder member has a forced fit and sealed connection to the lower end of the cylinder head *b* which is reduced to a diameter such that the tubes *a'* and *a''* are spaced apart to form an annular chamber between them. For the purpose of dividing this annular chamber into two sections *e* and *e'* the liner tube *a''* is formed with a suitably positioned enlarged or divider portion *a'''* of an external diameter which closely fits the internal diameter of tube *a'*. Sealing rings, which may be of any suitable form or material, are indicated at *a''* for sealing sections *e* and *e'* of the annular chamber from each other. Fig. 2 shows clearly the construction of the liner tube *a''* so far described.

The lower end of the outer tube *a'* of the cylinder member is internally threaded for connection to a drill bit guide member *f*, the upper end of which also has a forced fit and sealed connection to the lower end of the liner tube *a''*. The drill bit, indicated at *g*, has its shank *g'* slidably received within a central bore of the bit guide *f*, the shank *g'* and guide bore being correspondingly splined as

indicated at *h* for transmission of rotary motion from the bit guide to the drill bit. One side of the shank *g'* is also slotted at *i* to receive a pin *j* passing transversely through the bit guide *f*, the length of the slot being such as to permit a limited freedom of movement of the drill bit shank within and relative to the drill bit guide *f*.

Within the bore of the liner tube *a''* of the cylinder member *a*, between the cylinder head *b* and the drill bit guide *f*, there is operably located a hammer like piston member *k* for the purpose of giving rapid successive percussive blows to the drill bit *g*. The cylindrical surface of the piston *k* has two spaced apart circumferential grooves forming an upper groove *k'* and a lower groove *k''*. The upper groove *k'* is connected by an inclined passage or bore *m* to the cylinder space *n* located beneath the piston and above the drill bit guide *f*. In a similar manner the lower groove *k''* is connected by an inclined passage or bore *o* to the cylinder space *p* located above the piston and below the cylinder head *b*. The piston *k* has a projecting portion or tail *q* by means of which percussive blows developed by the piston can be transmitted to the end of the shank of the drill bit *g*.

In the liner tube *a''* of the cylinder member *a* there are formed compressed air inlet ports or passages *r* and air exhaust ports *s*. These inlet and exhaust ports are located at opposite sides of the divider portion *a'''* of liner tube *a''* (see Fig. 2), and are so positioned and spaced apart in the tube *a''* such that they can co-operate in sequence with the spaced apart grooves *k'* and *k''* of the piston *k* for effecting entry of compressed air into and exhaust from the cylinder spaces *n* and *p*. Compressed air for operating piston *k* is supplied by the boring plant compressor and passed through the bore of the hollow drill rod string from which it enters the bore *c'* of the drill rod connector *c* and passes through the bore of the cushion assembly *d* to a chamber *b'* in the cylinder head *b*. A series of inclined passages *b''* in the cylinder head lead the compressed air from chamber *b'* to section *e* of the annular chamber in the cylinder member. The lower end of section *e'* of the annular chamber in the cylinder member is open for passage of exhaust air therefrom to a passage or passages such as *f'* in the drill guide *f*, from which the air passes to the drill bit and borehole for cooling the bit and removing cuttings.

With the arrangement above described and the piston *k* and drill bit *g* in the position illustrated in Fig. 1, compressed air supplied to the drill rod string will pass through the bore of the drill rod connector *c* and cushion assembly *d* to the cylinder head chamber *b'* and passages *b''* and enter section *e* of the cylinder chamber. From the latter the compressed air passes through the inlet ports *r*

to the upper piston *k*, the cylinder resultant underside move up a short distance is cut off covered

piston *k* and *k'* exhaust passage or slot *k''*, and the cylinder

piston up into such *k''* passes thus the

to exhaust chamber sages *f'* in such up lower circle

the inlet passed by cylinder trapped

exerts a downward it has means and exhaust piston land by stoppi

the cylinder passage of the piston this position in the cylinder

pans and apply its drill bit guide *f*.

of the piston *k'* comes haust port cylinder through the annular chamber

passages *f'* piston has again in a and thus repeatedly

hammer like the supply rod string

The forms 3 and 4 in and differ cylinder liner member *o* used in Fig. 1 similar part

4, as in Fig. 1

f rotary
 drill bit.
 d at i to
 through
 ot being
 of move-
 and rela-
 70
 a' of the
 der head
 operably
 er k for
 ive per-
 he cylin-
 o spaced
 ning an
 k'. The
 inclined
 space n
 the drill
 he lower
 l passage
 located
 der head
 ortion or
 ve blows
 nitted to
 g.
 er mem-
 air inlet
 ports s.
 xcated at
 in a' of
 so posi-
 a' such
 with the
 ie piston
 air into
 n and p.
 k is sup-
 105
 100
 110
 115
 120
 125
 130
 135
 140
 145
 150
 155
 160
 165
 170
 175
 180
 185
 190
 195
 200
 205
 210
 215
 220
 225
 230
 235
 240
 245
 250
 255
 260
 265
 270
 275
 280
 285
 290
 295
 300
 305
 310
 315
 320
 325
 330
 335
 340
 345
 350
 355
 360
 365
 370
 375
 380
 385
 390
 395
 400
 405
 410
 415
 420
 425
 430
 435
 440
 445
 450
 455
 460
 465
 470
 475
 480
 485
 490
 495
 500
 505
 510
 515
 520
 525
 530
 535
 540
 545
 550
 555
 560
 565
 570
 575
 580
 585
 590
 595
 600
 605
 610
 615
 620
 625
 630
 635
 640
 645
 650
 655
 660
 665
 670
 675
 680
 685
 690
 695
 700
 705
 710
 715
 720
 725
 730
 735
 740
 745
 750
 755
 760
 765
 770
 775
 780
 785
 790
 795
 800
 805
 810
 815
 820
 825
 830
 835
 840
 845
 850
 855
 860
 865
 870
 875
 880
 885
 890
 895
 900
 905
 910
 915
 920
 925
 930
 935
 940
 945
 950
 955
 960
 965
 970
 975
 980
 985
 990
 995
 1000
 1005
 1010
 1015
 1020
 1025
 1030
 1035
 1040
 1045
 1050
 1055
 1060
 1065
 1070
 1075
 1080
 1085
 1090
 1095
 1100
 1105
 1110
 1115
 1120
 1125
 1130
 1135
 1140
 1145
 1150
 1155
 1160
 1165
 1170
 1175
 1180
 1185
 1190
 1195
 1200
 1205
 1210
 1215
 1220
 1225
 1230
 1235
 1240
 1245
 1250
 1255
 1260
 1265
 1270
 1275
 1280
 1285
 1290
 1295
 1300
 1305
 1310
 1315
 1320
 1325
 1330
 1335
 1340
 1345
 1350
 1355
 1360
 1365
 1370
 1375
 1380
 1385
 1390
 1395
 1400
 1405
 1410
 1415
 1420
 1425
 1430
 1435
 1440
 1445
 1450
 1455
 1460
 1465
 1470
 1475
 1480
 1485
 1490
 1495
 1500
 1505
 1510
 1515
 1520
 1525
 1530
 1535
 1540
 1545
 1550
 1555
 1560
 1565
 1570
 1575
 1580
 1585
 1590
 1595
 1600
 1605
 1610
 1615
 1620
 1625
 1630
 1635
 1640
 1645
 1650
 1655
 1660
 1665
 1670
 1675
 1680
 1685
 1690
 1695
 1700
 1705
 1710
 1715
 1720
 1725
 1730
 1735
 1740
 1745
 1750
 1755
 1760
 1765
 1770
 1775
 1780
 1785
 1790
 1795
 1800
 1805
 1810
 1815
 1820
 1825
 1830
 1835
 1840
 1845
 1850
 1855
 1860
 1865
 1870
 1875
 1880
 1885
 1890
 1895
 1900
 1905
 1910
 1915
 1920
 1925
 1930
 1935
 1940
 1945
 1950
 1955
 1960
 1965
 1970
 1975
 1980
 1985
 1990
 1995
 2000
 2005
 2010
 2015
 2020
 2025
 2030
 2035
 2040
 2045
 2050
 2055
 2060
 2065
 2070
 2075
 2080
 2085
 2090
 2095
 2100
 2105
 2110
 2115
 2120
 2125
 2130
 2135
 2140
 2145
 2150
 2155
 2160
 2165
 2170
 2175
 2180
 2185
 2190
 2195
 2200
 2205
 2210
 2215
 2220
 2225
 2230
 2235
 2240
 2245
 2250
 2255
 2260
 2265
 2270
 2275
 2280
 2285
 2290
 2295
 2300
 2305
 2310
 2315
 2320
 2325
 2330
 2335
 2340
 2345
 2350
 2355
 2360
 2365
 2370
 2375
 2380
 2385
 2390
 2395
 2400
 2405
 2410
 2415
 2420
 2425
 2430
 2435
 2440
 2445
 2450
 2455
 2460
 2465
 2470
 2475
 2480
 2485
 2490
 2495
 2500
 2505
 2510
 2515
 2520
 2525
 2530
 2535
 2540
 2545
 2550
 2555
 2560
 2565
 2570
 2575
 2580
 2585
 2590
 2595
 2600
 2605
 2610
 2615
 2620
 2625
 2630
 2635
 2640
 2645
 2650
 2655
 2660
 2665
 2670
 2675
 2680
 2685
 2690
 2695
 2700
 2705
 2710
 2715
 2720
 2725
 2730
 2735
 2740
 2745
 2750
 2755
 2760
 2765
 2770
 2775
 2780
 2785
 2790
 2795
 2800
 2805
 2810
 2815
 2820
 2825
 2830
 2835
 2840
 2845
 2850
 2855
 2860
 2865
 2870
 2875
 2880
 2885
 2890
 2895
 2900
 2905
 2910
 2915
 2920
 2925
 2930
 2935
 2940
 2945
 2950
 2955
 2960
 2965
 2970
 2975
 2980
 2985
 2990
 2995
 3000
 3005
 3010
 3015
 3020
 3025
 3030
 3035
 3040
 3045
 3050
 3055
 3060
 3065
 3070
 3075
 3080
 3085
 3090
 3095
 3100
 3105
 3110
 3115
 3120
 3125
 3130
 3135
 3140
 3145
 3150
 3155
 3160
 3165
 3170
 3175
 3180
 3185
 3190
 3195
 3200
 3205
 3210
 3215
 3220
 3225
 3230
 3235
 3240
 3245
 3250
 3255
 3260
 3265
 3270
 3275
 3280
 3285
 3290
 3295
 3300
 3305
 3310
 3315
 3320
 3325
 3330
 3335
 3340
 3345
 3350
 3355
 3360
 3365
 3370
 3375
 3380
 3385
 3390
 3395
 3400
 3405
 3410
 3415
 3420
 3425
 3430
 3435
 3440
 3445
 3450
 3455
 3460
 3465
 3470
 3475
 3480
 3485
 3490
 3495
 3500
 3505
 3510
 3515
 3520
 3525
 3530
 3535
 3540
 3545
 3550
 3555
 3560
 3565
 3570
 3575
 3580
 3585
 3590
 3595
 3600
 3605
 3610
 3615
 3620
 3625
 3630
 3635
 3640
 3645
 3650
 3655
 3660
 3665
 3670
 3675
 3680
 3685
 3690
 3695
 3700
 3705
 3710
 3715
 3720
 3725
 3730
 3735
 3740
 3745
 3750
 3755
 3760
 3765
 3770
 3775
 3780
 3785
 3790
 3795
 3800
 3805
 3810
 3815
 3820
 3825
 3830
 3835
 3840
 3845
 3850
 3855
 3860
 3865
 3870
 3875
 3880
 3885
 3890
 3895
 3900
 3905
 3910
 3915
 3920
 3925
 3930
 3935
 3940
 3945
 3950
 3955
 3960
 3965
 3970
 3975
 3980
 3985
 3990
 3995
 4000
 4005
 4010
 4015
 4020
 4025
 4030
 4035
 4040
 4045
 4050
 4055
 4060
 4065
 4070
 4075
 4080
 4085
 4090
 4095
 4100
 4105
 4110
 4115
 4120
 4125
 4130
 4135
 4140
 4145
 4150
 4155
 4160
 4165
 4170
 4175
 4180
 4185
 4190
 4195
 4200
 4205
 4210
 4215
 4220
 4225
 4230
 4235
 4240
 4245
 4250
 4255
 4260
 4265
 4270
 4275
 4280
 4285
 4290
 4295
 4300
 4305
 4310
 4315
 4320
 4325
 4330
 4335
 4340
 4345
 4350
 4355
 4360
 4365
 4370
 4375
 4380
 4385
 4390
 4395
 4400
 4405
 4410
 4415
 4420
 4425
 4430
 4435
 4440
 4445
 4450
 4455
 4460
 4465
 4470
 4475
 4480
 4485
 4490
 4495
 4500
 4505
 4510
 4515
 4520
 4525
 4530
 4535
 4540
 4545
 4550
 4555
 4560
 4565
 4570
 4575
 4580
 4585
 4590
 4595
 4600
 4605
 4610
 4615
 4620
 4625
 4630
 4635
 4640
 4645
 4650
 4655
 4660
 4665
 4670
 4675
 4680
 4685
 4690
 4695
 4700
 4705
 4710
 4715
 4720
 4725
 4730
 4735
 4740
 4745
 4750
 4755
 4760
 4765
 4770
 4775
 4780
 4785
 4790
 4795
 4800
 4805
 4810
 4815
 4820
 4825
 4830
 4835
 4840
 4845
 4850
 4855
 4860
 4865
 4870
 4875
 4880
 4885
 4890
 4895
 4900
 4905
 4910
 4915
 4920
 4925
 4930
 4935
 4940
 4945
 4950
 4955
 4960
 4965
 4970
 4975
 4980
 4985
 4990
 4995
 5000
 5005
 5010
 5015
 5020
 5025
 5030
 5035
 5040
 5045
 5050
 5055
 5060
 5065
 5070
 5075
 5080
 5085
 5090
 5095
 5100
 5105
 5110
 5115
 5120
 5125
 5130
 5135
 5140
 5145
 5150
 5155
 5160
 5165
 5170
 5175
 5180
 5185
 5190
 5195
 5200
 5205
 5210
 5215
 5220
 5225
 5230
 5235
 5240
 5245
 5250
 5255
 5260
 5265
 5270
 5275
 5280
 5285
 5290
 5295
 5300
 5305
 5310
 5315
 5320
 5325
 5330
 5335
 5340
 5345
 5350
 5355
 5360
 5365
 5370
 5375
 5380
 5385
 5390
 5395
 5400
 5405
 5410
 5415
 5420
 5425
 5430
 5435
 5440
 5445
 5450
 5455
 5460
 5465
 5470
 5475
 5480
 5485
 5490
 5495
 5500
 5505
 5510
 5515
 5520
 5525
 5530
 5535
 5540
 5545
 5550
 5555
 5560
 5565
 5570
 5575
 5580
 5585
 5590
 5595
 5600
 5605
 5610
 5615
 5620
 5625
 5630
 5635
 5640
 5645
 5650
 5655
 5660
 5665
 5670
 5675
 5680
 5685
 5690
 5695
 5700
 5705
 5710
 5715
 5720
 5725
 5730
 5735
 5740
 5745
 5750
 5755
 5760
 5765
 5770
 5775
 5780
 5785
 5790
 5795
 5800
 5805
 5810
 5815
 5820
 5825
 5830
 5835
 5840
 5845
 5850
 5855
 5860
 5865
 5870
 5875
 5880
 5885
 5890
 5895
 5900
 5905
 5910
 5915
 5920
 5925
 5930
 5935
 5940
 5945
 5950
 5955
 5960
 5965
 5970
 5975
 5980
 5985
 5990
 5995
 6000
 6005
 6010
 6015
 6020
 6025
 6030
 6035
 6040
 6045
 6050
 6055
 6060
 6065
 6070
 6075
 6080
 6085
 6090
 6095
 6100
 6105
 6110
 6115
 6120
 6125
 6130
 6135
 6140
 6145
 6150
 6155
 6160
 6165
 6170
 6175
 6180
 6185
 6190
 6195
 6200
 6205
 6210
 6215
 6220
 6225
 6230
 6235
 6240
 6245
 6250
 6255
 6260
 6265
 6270
 6275
 6280
 6285
 6290
 6295
 6300
 6305
 6310
 6315
 6320
 6325
 6330
 6335
 6340
 6345
 6350
 6355
 6360
 6365
 6370
 6375
 6380
 6385
 6390
 6395
 6400
 6405
 6410
 6415
 6420
 6425
 6430
 6435
 6440
 6445
 6450
 6455
 6460
 6465
 6470
 6475
 6480
 6485
 6490
 6495
 6500
 6505
 6510
 6515
 6520
 6525
 6530
 6535
 6540
 6545
 6550
 6555
 6560
 6565
 6570
 6575
 6580
 6585
 6590
 6595
 6600
 6605
 6610
 6615
 6620
 6625
 6630
 6635
 6640
 6645
 6650
 6655
 6660
 6665
 6670
 6675
 6680
 6685
 6690
 6695
 6700
 6705
 6710
 6715
 6720
 6725
 6730
 6735
 6740
 6745
 6750
 6755
 6760
 6765
 6770
 6775
 6780
 6785
 6790
 6795
 6800
 6805
 6810
 6815
 6820
 6825
 6830
 6835
 6840
 6845
 6850
 6855
 6860
 6865
 6870
 6

inlet ports *v* and thus compressed air is passed by way of bore *o* to cylinder space *p* above the piston to cause downward movement of the latter. After the piston has moved down a short distance the inlet and exhaust ports *v* and *w* are cut off by the land *k*² and skirt *k*¹ respectively, thereby stopping supply of compressed air to the cylinder space *p* and the passage of air from cylinder space *n* to exhaust through ports *w*. In this position the entrapped air in cylinder space *p* expands and forces the piston downwards to apply its hammer blow to the drill bit *g*. During the downward movement of the piston the skirt *k*¹ uncovers exhaust ports *w* to allow the air in cylinder space *p* to pass to exhaust. When the piston has applied its percussive blow it is again in a position to repeat the above cycle.

In the form of the invention illustrated in Figs. 5 and 6 the cylinder member 2 is adapted for convection to a driving quill 3 by means of an adaptor plate 4. The latter is secured by screws 5 to a flange 6 formed on one end of cylinder 2, and by screws 8 to the quill flange 9. The quill 3 receives a rotary and feed motion for transmission to the drill rod string, and this may be provided in any known manner, such as for example by a rotary drill head supported by a carriage which is movable along a base frame to provide the feed motion. A portion of such a carriage, to be referred to later, is indicated at 10. The other, outer, end of cylinder 2 is adapted for connection to the first drill rod of the drill rod string by means of a two-part telescoping unit, one part 11 of which has a flange 12 secured by screws 13 to the outer end of cylinder 2. The other telescoping part of the telescoping unit has a central portion 14 slidable within a bore of part 11 and an extension or stem 15 provided at its outer end with a tapered screw thread 16 for receiving the correspondingly screw-threaded end of the first drill rod (not shown) of the drill rod string. A further extension or stem 17 of the telescoping part 11 projects within cylinder 12 and is splined or keyed at 18 to part 11 of the telescoping unit so that it can receive the rotary motion of the cylinder 2 provided by quill 3.

Within the bore of cylinder 2 there is operably located a hammer like piston member 19 for giving rapid successive percussive blows to the drill bit through the intermediary of the telescoping or sliding part of the telescoping unit and its attached drill rod string, to the outer end of which the drill bit is secured. The cylindrical surface of the piston 19 has two spaced apart circumferential grooves 20 and 21, the former of which is connected by radial and longitudinal bores 22 in the piston to a cylinder space 23 located between one end of the piston and one end of the telescoping unit. The groove 21

is connected by radial and longitudinal bores 24 in the piston to a cylinder space 25 located between the other end of the piston and the cylinder adaptor plate 4.

In the wall of the cylinder 2 there are formed compressed air inlet ports 26 and air exhaust ports 27 which are so positioned and spaced apart in the cylinder wall such that they can co-operate in sequence with the spaced apart grooves 20 and 21 of the piston 19 for effecting entry of compressed air and exhaust from the cylinder spaces 23 and 25. For supply and exhaust of compressed air a non-rotatory air swivel assembly is provided consisting of a sleeve 28 surrounding and spaced from the cylinder wall to form an annular chamber divided by an oil seal 29 into a compressed air supply section 30 and an air exhaust section 31. The inlet ports 26 in the cylinder wall open into compressed air supply section 30, while the exhaust ports 27 open into air exhaust section 31. Bushings 32 at each end of the sleeve 28 provide bearings for rotation of cylinder 2 within the sleeve, and further oil seals 33 serve to seal these bearings against escape of air from the sleeve sections 30 and 31. Compressed air for operating piston 19 is supplied by the boring plant compressor and passed to a compressed air inlet connection 34 provided upon sleeve 28 leading to compressed air supply section 30 of the sleeve. An air exhaust connection for exhaust section 31 of the sleeve is indicated at 35. Sleeve 28 may be prevented from rotation in any suitable manner, and for the purpose of illustration is shown provided with a boss 36 supporting a steady or guide pin 37. The latter contacts a guide 38 mounted upon the carriage 10 which supports a rotary drill head previously referred to.

The operation of the apparatus of Figs. 5 and 6 is similar to that of the apparatus of Figs. 3 and 4, compressed air supplied to section 30 of the sleeve passing through inlet ports 26, groove 20 and bores 22 to cylinder space 23 to move the piston 19 in a direction towards adaptor plate 4, to a position in which the land 39 of the piston cuts off the compressed air supply from inlet ports 26. In this position the entrapped compressed air in cylinder space 23 expands and drives the piston to a further position in which piston groove 20 coincides with exhaust ports 27 to exhaust cylinder space 23. Further, in this piston position piston groove 21 coincides with inlet ports 26 to pass compressed air via bores 24 to cylinder space 25 to move piston 19 in a reverse direction to a position in which piston land 39 cuts off compressed air supply from inlet ports 26. Consequently the entrapped air in cylinder space 25 expands and moves the piston with a force to apply its hammer blow to extension 17 of telescoping part 11 and thus through the drill

rod string moves to on the p exhaust c has appli position 1

It will by the in for apply: of earth (is provide parts, no instead of hammer l will func vertically for exami defective

WHAT 1. App: to the dri drilling member : rod string operating exhaust f sage of a passage r controlling to and fr said inlet opening a trolled by ment of t a manner member l drill bit.

2. App: means mo movement ceiving th member a or indirec the drill l 3. Appa 2, having ber servir compressed cylinder s member, member s: air to a c end of the latter cyli skirt on sa ber.

4. App: claim, wl adapted fo the outer and an ex and mova end of the tail portio the percus

lial and longitudinal bores a cylinder space 25 located end of the piston and the ate 4.

the cylinder 2 there are 70
air inlet ports 26 and air
hich are so positioned and
ie cylinder wall such that
te in sequence with the
es 20 and 21 of the piston 75
try of compressed air and
ylinder spaces 23 and 25.
haust of compressed air a
vivel assembly is provided
eeve 28 surrounding and 80
cylinder wall to form an
lvided by an oil seal 29
air supply section 30 and
tion 31. The inlet ports
wall open into compressed 85
30, while the exhaust ports
xhaust section 31. Bush-
d of the sleeve 28 provide
n of cylinder 2 within the
oil seals 33 serve to seal 90
nst escape of air from the
and 31. Compressed air
on 19 is supplied by the
essor and passed to a com-
nection 34 provided upon
to compressed air supply 95
leeve. An air exhaust con-
section 31 of the sleeve is
Sleeve 28 may be pre- 100
on in any suitable manner,
se of illustration is shown
oss 36 supporting a steady
The latter contacts a guide
the carriage 10 which sup-
ll head previously referred 105

of the apparatus of Figs. 5
o that of the apparatus of
ompressed air supplied to
leeve passing through inlet 110
0 and bores 22 to cylinder
the piston 19 in a direction
plate 4, to a position in
of the piston cuts off the
ply from inlet ports 26. In 115
ntrapped compressed air in
expands and drives the
r position in which piston
s with exhaust ports 27 to
pace 23. Further, in this 120
iston groove 21 coincides
to pass compressed air via
er space 25 to move piston
direction to a position in
39 cuts off compressed air 125
ports 26. Consequently
in cylinder space 25 ex-
the piston with a force to
blow to extension 17 of
and thus through the drill 130

rod string to the drill bit. As the piston moves to apply its hammer blow a skirt 40 on the piston uncovers exhaust ports 27 to exhaust cylinder space 25. When the piston has applied its percussive blow it is again in position to repeat the above cycle.

It will be appreciated from the above that by the invention a simple form of apparatus for applying percussive blows to the drill bit of earth or like boring or drilling mechanism is provided which has a minimum of moving parts, no moving valves being necessary but instead only ports covered or exposed by the hammer like piston. Further, the apparatus will function at all angles of use, including vertically upwards, and is easily dismantled for examination and replacement of worn or defective parts.

WHAT WE CLAIM IS:—

20 1. Apparatus for applying percussive blows to the drill bit of earth and the like boring or drilling apparatus comprising a cylinder member adapted for connection to the drill rod string, a hammer like piston member 25
operating in said cylinder member, inlet and exhaust ports in the cylinder wall for pas-
sage of a pressurized gaseous medium, and passage means in said piston member for controlling passage of said gaseous medium to and from said cylinder member through 30
said inlet and exhaust ports respectively, the opening and closing of said ports being controlled by said piston member during move-
ment of the latter by the gaseous medium in a manner whereby the hammer like piston member provides percussive blows for the drill bit.

2. Apparatus according to claim 1 having means mounted on the cylinder member for movement relative thereto, said means re-
ceiving the percussive blows of the piston member and transmitting the same directly, or indirectly through the drill rod string, to the drill bit.

3. Apparatus according to claim 1 or claim 2, having passage means in the piston mem-
ber serving for both inlet and exhaust of compressed air to and from respectively a cylinder space adjacent one end of the piston member, and passage means in the piston member serving only for inlet of compressed air to a cylinder space adjacent the opposite end of the piston member, exhaust from the latter cylinder space being controlled by a skirt on said opposite end of the piston mem-
ber.

4. Apparatus according to any preceding claim, wherein the cylinder member is adapted for connection to the last drill rod at the outer or lower end of the drill rod string, and an extension of the drill bit is carried by and movable relative to the outer or lower end of the cylinder member, a projecting or tail portion of the piston member applying the percussive blows to the drill bit extension.

5. Apparatus according to any preceding claim, wherein the cylinder member com-
prises inner and outer tubular members spaced apart to form an annular chamber divided into compressed air supply and ex-
haust sections, the inlet and exhaust ports being formed in the inner tubular member and opening into said supply and exhaust sections of the annular chamber respectively, the compressed air being supplied through a bore of the drill rod string to passage means formed in a cylinder head and leading to the supply section of the annular chamber.

6. Apparatus according to claim 5, where-
in the annular chamber of the cylinder is divided into said sections by a divider mem-
ber formed upon or integral with the inner tubular member and of a diameter fitting the internal diameter of the outer tubular mem-
ber, said divider member being positioned between the inlet and exhaust ports and having sealings rings for sealing said sections of the annular chamber from each other.

7. Apparatus according to claim 5, having the annular chamber of the cylinder divided into said sections by a divider member formed upon or integral with the inner tubular member and of a diameter fitting the internal diameter of the outer tubular mem-
ber, diametrically opposed cut-away portions projecting longitudinally, and in opposed directions commencing from opposite ends, of said divider member, inlet and outlet ports located in the cut-away portions and leading to the compressed air supply and exhaust sections respectively of said annular chamber and sealing means seated in the divider mem-
ber and of endless form as it passes between the cut-away portions and around ends there-
of.

8. Apparatus according to claim 5 or claim 6, having the cylindrical surface of the piston member formed with two spaced apart circum-
ferential grooves, passage means in the piston member connecting one groove to a cylinder space located at one end of said member, passages means in the piston member connecting the other groove to a cylinder space located at the other end of said member, a skirt at one end of the piston member and a projecting portion or tail projecting from said skirt for applying to the drill bit the hammer blows developed by the piston member.

9. Apparatus according to claim 5 or claim 7, having the cylindrical surface of the piston member formed with two spaced apart circum-
ferential grooves, passage means in the piston member connecting one groove to a cylinder space located at one end of said member, passage means in the piston member connecting the other groove to cylinder space located at the other end of said member, a skirt at one end of the piston member and a projecting portion or tail projecting from the other end of the piston member for apply-

10. Apparatus according to any one of the preceding claims 5 to 9, having outer ends of the inner and outer tubular members secured to a drill bit guide, a central bore within said guide for slidably receiving an extension or shank of the drill bit, said shank being keyed or splined within said bore for transmission of rotary motion from the bit guide to the drill bit, and pin and slot means in said guide and shank for permitting limited sliding movement of the shank within the guide.


11. Apparatus according to any one of the preceding claims 1 to 3, wherein one end of the cylinder member is connected to one part of a two-part telescoping unit, the other part of which is adapted for connection to the first drill rod of the drill rod string, and the other end of the cylinder is connected to a driving quill providing the rotary and feed motion to the drill rod string, the hammer like piston member applying the percussive blows to an extension or stem portion of said other part of the two-part telescoping unit and thus through the drill rod string to the drill bit.

12. Apparatus according to claim 11, wherein the cylinder member rotates within a non-rotatory air swivel assembly comprising

13. Apparatus according to claim 11 or claim 12, having the cylindrical surface of the piston member formed with two spaced apart circumferential grooves, passage means in the piston member connecting one groove to a cylinder space located at one end of said member, passage means in the piston member connecting the other groove to a cylinder space located at the other end of said member, and a skirt at one end of the piston member the other end of which applies the percussive blows to the extension or stem portion of said other part of the two part telescoping unit and thus through the drill rod string to the drill bit.

14. Apparatus for applying percussive blows to the drill bit of earth and the like boring or drilling apparatus substantially as described with reference to the Figures 1 and 2, or Figs. 3 and 4 or Figs. 5 and 6 of the accompanying draws.

MARKS & CLERK.,
Chartered Patent Agents,
Agents for the Applicant(s).




ber surrounding and spaced
 der member to form an annular
 led into a compressed air
 and an air exhaust section into
 t and exhaust ports of the
 er open respectively.
 is according to claim 11 or
 the cylindrical surface of the
 formed with two spaced apart
 grooves, passage means in the
 connecting one groove to a
 located at one end of said
 means in the piston mem-
 ie other groove to a cylinder
 the other end of said mem-
 one end of the piston mem-
 of which applies the percus-
 extension or stem portion
 of the two part telescoping
 ough the drill rod string to

for applying percussive
 bit of earth and the like
 apparatus substantially as
 55
 1 or Figs. 5 and 6 of the
 s.

& CLERK,
 Patent Agents,
 the Applicant(s).
 Press.—1964.
 in which copies may be obtained.

962127 COMPLETE SPECIFICATION
 2 SHEETS This drawing is a reproduction of
 the Original on a reduced scale
 Sheet 1






Fig. 5.




Fig. 6.